

**Product Name :**  
Sequential Numbering Machine

**Product Code :**  
EQUP-MC20087-0050



**Description :**

Sequential Numbering Machine

**Technical Specification :**

Color Black  
Grade Industrial  
Voltage (Volt) 220 V  
Size 12X19X8 cm & 30X19X60 cm with stand  
Weight 3 Kgs for machine & 15 Kgs with stand  
Impression Appx. 90 million char. of 2 mm per lit. of ink  
Print distance Max. 5 mm Down or in Front

**Sequential Numbering Machine** which High Speed Coding on packaging machines or bottles moving on conveyor or Winder / Rewinder systems. The 1 to 8 line message to be printed is easily composed on its Colored Touch Screen Graphic display with a combination of small, medium or large characters along with LOGOs, Objects & Scannable Bar Codes. The Inking system consists of disposable pre-mix ink cartridge using fast drying & indelible solvent-based inks (for porous and non-porous surfaces) which are push fitted into its slot to immediately start printing.

**Features:**

- Stainless steel rugged construction. All machine stands, product sensor with stand, print head stand included with the system. Connection to print head via 2 m flexible cable. The print module is well protected & insulated in the Stainless steel tubular print head
- Graphic 8.4" WYSIWYG Colored backlit liquid crystal Touch Screen Display with Real time clock and

calendar, expiry date, Scannable Bar Codes, LOGOs, Serial nos. (Counter), with 9 levels of Bolderisation, message reverse or invert print & storage of 256 messages of 1 to 8 lines each of 120 characters per line with facility for password lock

- Push fit disposable solvent / oil based pre-mix ink cartridge for ease of use. Uses Ethyl alcohol based simple inks that do not require any mixing or viscosity adjustments
- Latest technology high speed 128 nozzle, 18 mm XAAR Piezo-jet print head which is very high resolution & gives very high quality of print
- Instant startup within 1 minute for the first print & instant shutdown within 1 minute with print head cleaning. Other printers require upto 30 minutes for each of the procedures & require a trained engineer
- The system is PC linkable via the USB or Wi-Fi for downloading of Logos, Fonts, data, etc. using Remote Manager or Flexicode software

Supply Voltage	90 to 220 Vac $\pm$ 10%, 50/60 Hz, 50 VA
Operating Range	0 to 45 deg. C, 10 – 90% RH non-condensing.
Printing Area	8 lines of 120 char each from 1 to 18 mm high.
Printing Speed	Max. 65 Meters / min. for 1 to 8 line printing.
Prints using	Piezo-electric print head for spraying ink.
Print Distance	Max. 5 mm Down or in Front.
Inking Medium	Disposable pre-mix ink cartridge
Printing Medium	Solvent based inks (black, blue, white*, etc.)
Ink Drying Time	Min. 10 seconds on plastic, metal & laminates.
Impressions	Appx. 90 million char. of 2 mm per lit. of ink.
Dimensions	12X19X8 cm & 30X19X60 cm with stand.
Weight	3 Kgs for machine & 15 Kgs with stand



## Equipments Machines Manufacturers