

Product Name :
Inkjet Batch Coding Machine

Product Code :
EQUP-MC20086-0050



Description :

Inkjet Batch Coding Machine

Technical Specification :

Ink Type Ink Types
Capacity Variabal
Material Variable
Display Type Digital
Automation Grade Automatic
Display Digital
Frequency 50-60
Voltage 180 V
Weight Unpacked and dry 39.68 lbs. (18 kg)
Power 100-120 / 200-240 VAC at 50/60 Hz., 120 W
Data Matrix 0% to 90% RH non-condensing
Size 8-10 mm

| | |
|------------------|--|
| Display | 4.3" full color Touch Screen LCD with LED backlight. |
| Languages | English, Spanish, French, German, Chinese, etc. |
| Input Device | 800 x 480 Touch Screen LCD, Pen Drive. |
| Printable Images | Alphanumeric, Logo, Date/Time, Counter, Barcode, etc. UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, |

| | |
|--------------------|---|
| Printing Area | ENA128, PDF417, DATAMATRIX, QR 1 to 6 lines of 2000 characters from 1.2 to 12.7 mm high. |
| Printing Direction | Adjustable at any angle within 360 degree |
| Message Capacity | Store upto 999 messages with Message Name. |
| Printing Speed | Max. 70 meters/min for 1 to 6 line printing at 300 dpi |
| Prints Using | Hewlett-Packard (hp) TIJ 2.5 Print-head for spraying ink |
| Print Distance | Max. 6 mm from substrate down or in front. |
| Inking Medium | 42 cc disposable pre-mix ink in Cartridge form with head. |
| Printing Medium | Solvent/Oil based inks (black, white, red, blue, yellow, etc.) |
| Ink Drying Time | Min. 5 seconds on plastics & laminates. |
| Impressions | Appx. 25 Lakh characters of 2 mm per cartridge of ink. |
| Operating Range | 10 ~ +38°C 10% - 80% RH, non-condensing. |
| Supply Voltage | 90 - 240 Vac, 50/60 Hz, 5 W |
| Battery Voltage | 16.8V lithium battery, 10 hours use / 20 hours standby |
| Dimensions | H130 x W128 x D20 mm |
| Weight | 1.2 Kg excluding cartridge & battery. |



Equipments Machines Manufacturers